LED SPECIFICATION

LED-010-25025


➢ Features：

- Single color
- High bright output
- Low power consumption
- High reliability and long life


➢ Descriptions：

- Dice material：AlGaInP
- Emitting Color：Super Bright Red
- Device Outline： ϕ5mm Round Type
- Lens Type：Water Clear

➢ Directivity：



1. All dimensions are millimeters
2. Tolerance is +/-0.25mm unless otherwise noted



LED SPECIFICATION

➢ Absolute maximum ratings（Ta = 25℃）

Parameter	Symbol	Test Condition	Values		Unit
			Min.	Max.	
Reverse Voltage	V_R	I_R = 30μA	5	--	V
Forward Current	I_F	----	----	30	mA
Power Dissipation	P_d	----	----	75	mW
Pulse Current	I_{peak}	Duty=0.1mS，1kHz	----	100	mA
Operating Temperature	T_{opr}	----	-20	+85	℃
Storage Temperature	T_{str}	----	-25	+100	℃

➢ Electrical and optical characteristics（Ta = 25℃）

Parameter	Symbol	Test Condition	Values			Unit
			Min.	Typ.	Max.	
Forward Voltage	V_F	I_F=20mA	----	2.2	2.6	V
Reverse Current	I_R	V_R=5V	----	----	30	μA
Dominate Wavelength	λ_d	I_F=20mA	620	626	630	nm
Peak Wavelength	λ_p	I_F=20mA	----	632	----	nm
Spectral Line half-width	$\Delta\lambda$	I_F=20mA	----	20	----	nm
Luminous Intensity	I_V	I_F=20mA		BIN	----	mcd
Viewing Angle	$2\theta_{1/2}$	I_F=20mA	----	40	----	deg.

➢ Luminous Intensity Bins（Ta = 25℃）

Unit:mcd

Bin	U	V	W	X
Min			3000	4180
Max			4180	5160

➢ Typical electrical/optical characteristic curves：

