PARANA 274 (C1017AAF) BUENOS AIRES TEL/FAX: 4371-5300 (L.ROT) www.sycelectronica.com.ar info@sycelectronica.com.ar

CODIGO DESCRIPCION MKTXXX-XXX-10

Metallized Polyester Film Capacitor, BOX TYPE MKT are non-inductively wound with Metallized Polyester film as dielectric and encapsulated in plastic case with epoxy resin filled.

Features

- High moisture resistance.
- Good solder ability.
- Self-healing properties.
- Space-saving small size.


Specifications

1. Operating Temperature: -40°C \sim +85°C Capacitance Range: 0.01 μF ~ 1.0 μF 3. Capacitance Tolerance: ±5%(J), ±10%(K)

250VDC, 400VDC, 630VDC 4. Rated Voltage:

Dissipation Factor: ¶ 1.0% max. at 1KHz, 25℃ 6. Insulation Resistance: >30,000 M Ω (C ≤ 0.33 μ F).

 $> 10,000 \text{ M}\Omega\text{F/C} (C > 0.33 \mu\text{ F}).$



Poliester metalizado

Ш	п	è	m	r
_	•••	_		_

	RV	250VDC					400VDC					630VDC				
	CAP(uF)	w	π	Т	Р	dø	w	Ι	Т	Р	dø	W	н	Т	Р	dø
	0.010						13.0	11.0	5.0	10.0	0.6	13.0	11.0	5.0	10.0	0.6
	0.015						13.0	11.0	5.0	10.0	0.6	13.0	11.0	5.0	10.0	0.6
	0.022				10.10		13.0	11.0	5.0	10.0	0.6	13.0	11.0	5.0	10.0	0.6
	0.033						13.0	11.0	5.0	10.0	0.6	13.0	12.0	6.0	10.0	0.6
	0.047	13.0	11.0	5.0	10.0	0.6	13.0	11.0	5.0	10.0	0.6	18.0	11.0	5.0	15.0	0.8
	0.056	13.0	11.0	5.0	10.0	0.6	13.0	11.0	5.0	10.0	0.6	18.0	11.0	5.0	15.0	0.8
	0.068	13.0	11.0	5.0	10.0	0.6	13.0	12.0	6.0	10.0	0.6	18.0	12.0	6.0	15.0	0.8
	0.082	13.0	11.0	5.0	10.0	0.6	13.0	12.0	6.0	10.0	0.6	18.0	13.5	7.5	15.0	0.8
100	0.10	13.0	11.0	5.0	10.0	0.6	18.0	11.0	5.0	15.0	8.0	18.0	13.5	7.5	15.0	0.8
	0.15	13.0	11.0	5.0	10.0	0.6	18.0	12.0	6.0	15.0	8.0					
	0.22	18.0	11.0	5.0	15.0	8.0	18.0	13.5	7.5	15.0	8.0					
Г	0.33	18.0	11.0	5.0	15.0	0.8	18.5	16.0	10.0	15.0	8.0					
	0.47	18.0	12.0	6.0	15.0	0.8	26.5	16.5	7.0	22.5	8.0					
	0.56	18.0	12.0	6.0	15.0	8.0					22,77					
	0.68	18.0	13.5	7.5	15.0	0.8										
	0.82	18.0	13.5	7.5	15.0	8.0										
L	1.00	18.0	14.5	7.5	15.0	8.0										